

Ordering Information

Model Number
WK - [] - [] - [] - **E** - [] - []

Panel Type

- F** BNC, Non-recessed
- G** BNC, Semi-recessed
- H** F Connector

Number of Rows of Jacks

- 1** 1 Row of Jacks
- 2** 2 Rows of Jacks, 1.5 & 2 RU Panels Only
- 3** 3 Rows of Jacks, 2 RU Panels Only

Number of Jacks per Row

- 16** 16 Jacks per row
- 20** 20 Jacks per row
- 24** 24 Jacks per row*

*Semi-recessed not available in 24 position

Cable Bar Option

- BZ** No Cable Bar
- B19** 3" [81mm] Cable Bar for 1RU only
- B22** 6" [152mm] Cable Bar for 1RU only
- B17B** 3" [81mm] Cable Bar for 1.5 & 2RU only
- B21B** 6" [152mm] Cable Bar for 1.5 & 2RU only

Installed Jacks

- JJ300** JJ300 BNC-BNC Connectors, 12GHz
- JJ200** JJ200 BNC-BNC Connectors, 3GHz
- HF310** HF310 F-F Connectors
- Z** None (Empty Panel)

Panel Height

- 1** 1 Rack Unit 1.75", 44mm
- 15** 1.5 Rack Unit 2.62", 66mm
- 2** 2 Rack Unit 3.50", 89mm

Designation Layouts...
www.jackfields.com/support




WK-G216E2-JJ300-B21B
shown

Popular Models (Configurations up to 3x24 are available)

Model	Description
BNC-BNC Non-recessed Connector Panels	
WK-F116E1-JJ300-BZ	1RU, 1x16 position, BNC-BNC non-recessed panel, 16 JJ300 12GHz connectors, no cable bar
WK-F216E2-JJ300-BZ	2RU, 2x16 position, BNC-BNC non-recessed panel, 32 JJ300 12GHz connectors, no cable bar
WK-F320E2-JJ300-BZ	2RU, 3x20 position, BNC-BNC non-recessed panel, 60 JJ300 12GHz connectors, no cable bar
WK-F216E2-Z-BZ	2RU, 2x16 position, BNC-BNC non-recessed panel, empty, no cable bar
BNC-BNC Semi-recessed Connector Panels	
WK-G116E1-JJ300-BZ	1RU, 1x16 position, BNC-BNC semi-recessed panel, 16 JJ300 12GHz connectors, no cable bar
WK-G216E2-JJ300-BZ	2RU, 2x16 position, BNC-BNC semi-recessed panel, 32 JJ300 12GHz connectors, no cable bar
WK-G320E2-JJ300-BZ	2RU, 3x20 position, BNC-BNC semi-recessed panel, 60 JJ300 12GHz connectors, no cable bar
WK-G216E2-Z-BZ	2RU, 2x16 position, BNC-BNC semi-recessed panel, empty, no cable bar
F-F Connector Panels	
WK-H116E1-HF310-BZ	1RU, 1x16 position, F connector panel, 16 HF310 connectors, no cable bar
WK-H216E2-HF310-BZ	2RU, 2x16 position, F connector panel, 32 HF310 connectors, no cable bar
WK-H324E2-HF310-BZ	2RU, 3x24 position, F connector panel, 72 HF310 connectors, no cable bar


F Connector Specifications




Description: High Performance F-81 Barrel Splice
Body Material: 360 Grade Brass, Bright Nickel Plated
Overall Length: 1.026" (26.06mm)
Hex Size: 0.44" (11.18mm)
Nut Width: 0.147" (37.34)
Insulator Material: Polypropylene
Center Pin Material: Beryllium Copper



BNC to BNC Connector Specifications



Description: 75 ohm Double BNC Female Bulkhead
Body Material: Brass, Bright Nickel Plated
Overall Length: 1.295" [32.90mm]
Barrel Diameter: 0.378" [9.60mm]
Nut Width: 0.551" [14.00mm]
Dielectric: Teflon, T-02015
Center Pin: Brass, Gold Plated



Description: 75 ohm Double BNC Female Bulkhead
Body Material: Brass, Bright Nickel Plated
Overall Length: 1.295" [32.90mm]
Barrel Diameter: 0.378" [9.60mm]
Nut Width: 0.551" [14.00mm]
Dielectric: Teflon, T-02015
Center Pin: Brass, Gold Flash

